

1

2

3

4

A

B

C

A

B

C












GROUND FLOOR PLAN
FURNITURE LAYOUT

Attachment No. 03

GROUND FLOOR PLAN R 1:50

LEGEND OF SPACES						
No	Room name	Floor processing	Wall processing	ceiling processing		Area m²
01	Terrace	Ceramic tiles	Semi-dispersion	Semi-dispersion		9,03
02	Hallway	Ceramic tiles	Semi-dispersion	Semi-dispersion		6,07
03	Bedroom	Parquet	Semi-dispersion	Semi-dispersion		12,00
04	Bathroom	Ceramic tiles	Ceramic tiles	Semi-dispersion		4,36
05	Bedroom	Parquet	Semi-dispersion	Semi-dispersion		11,58
06	Living room with kitchen and din. ar.	Parquet and tiles	Semi-dispersion and ceramic tiles	Semi-dispersion		30,67
TOTAL NET:						73,98
TOTAL GROSS:						86,44

BUILDING PHYSICS LEGEND		
 FG1 - Floor on Ground (Parquet) - Parquet on adhesive, d = 2.2cm - Cement screed, d = 4.8cm - Sound insulation (EPS), d = 2+2cm	 LDP - Layers of a Dead Plate - Concrete slab, d = 10cm - Gravel, d = 10cm - Crushed stone, d = 40cm - Soil	 Tr - Terrace - Ceramic tiles on adhesive, d = 3cm - Waterproofing - Cement screed, d = 7cm - Concrete slab, d = 10cm
 Reinforced Concrete Vertical Stirrup	 Reinforced Concrete Horizontal Stirrup	 RS - Roof Structure - Roof tiles - Cross battens, 4x5 cm - Longitudinal batten for ventilation layer, 8x4 cm - Vapor-permeable, waterproof membrane - OSB board, d = 20 mm - Under the rafters, boards with d = 2.5 cm are nailed, and over the boards and rafters, a vapor-permeable, waterproof membrane is placed, over which mineral wool with d= 10 cm is installed between the rafters. - Rafters, 14x14 cm - Ridge beam, 14x14 cm
 EW - Exterior Wall, d = 20cm (compact facade) - Semi-dispersive paint - Putty mass - Render coat (1:3:9), d = 2cm - Brick block 25/19/19cm or RC wall, d = 20cm - Thermal insulation (e.g., EPS), glued and anchored, d = 8cm - Adhesive - Glass fiber mesh - Adhesive - Impregnating primer - Final render coat	 IW1 - Interior Wall, d = 20cm (lightweight block) - Semi-dispersive paint - Putty mass - Render coat (1:3:9), d = 2cm - Brick block 20/19/19cm or RC wall, d = 20cm - Render coat (1:3:9), d = 2cm - Putty mass - Semi-dispersive paint	 IW2 - Interior Wall, d = 12cm (lightweight block) - Semi-dispersive paint - Putty mass - Render coat (1:3:9), d = 2cm - Brick block 20/19/12cm - Render coat (1:3:9), d = 2cm - Putty mass - Semi-dispersive paint